



ARM	Hole in arm	A (90°)		A (max)		B (max)		C*		D*		E**		F**		G		H		I		Weight	
		mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in
110-280	1	260	6.6	420	16.5	193	7.6	305	12	609	24	318	12.5	274	10.8	30	1.2	20	0.79	16	0.63	13.5	29.8
	2	270	6.9	500	19.7	280	11			696	27.4	335	13.2	283	11.1								
110-390	1	260	10.2	390	15.4	215	8.5			630	25	335	13.2	283	11.1								
	2	280	11	500	19.7	302	11.9			717	28.4	360	14.2	295	11.6								
110-490	3	300	11.8	600	23.6	390	15.4			805	31.8	380	15	305	12								
	1	320	8.1	330	13	228	9			643	25.3	378	14.9	304	12			17	0.67	15	0.59	17.3	38.1
	2	380	15	500	19.7	360	14.2	775	30.5	440	17.3	335	13.2										
3	430	16.9	700	27.6	490	19.3	905	35.6	495	19.5	363	14.3											

* With CFC1012
 ** @ A (90°)

Material	Blank, dimension	Heat treatment	Surface treatment
Permissible deviations for dimensions without indication of tolerances		Surface roughness unless specified	
Machined parts acc. SS-ISO 2768-1	Castings acc. SS-ISO 8062	Fuse welded constr. acc. SS-EN ISO 13920	Replaces
Designed by CS1	Drawn by CS1	Date 2016-06-13	Product AH110 10T Puller
Prod. appr. 2016-11-07	Design appr. cs1 2016-11-03	Scale 1:2	Title Dimension drawing
REHOBOT			A-51268